



20ft DRY

Internal Dimension

Length	5,897 mm	19 ft 4.17 in
Width	2,348 mm	7 ft 8.44 in
Height	2,390 mm	7 ft 9.90 in

Door Opening

Width	2,336 mm	7 ft 8.01 in
Height	2,280 mm	7 ft 5.45 in

Weight

Max Gross	30,480 kg (24,000 kg)	67,200 lb (52,910 lb)
Tare	2,240 kg (2,290 kg)	4,940 lb (5,050 lb)
Max Payload	28,240 kg (21,710 kg)	62,260 lb (47,860 lb)
Load Capacity	33.0 cubic meters	1,169 cubic feet



40ft DRY

Internal Dimension

Length	12,031 mm	39 ft 5.66 in
Width	2,348 mm	7 ft 8.44 in
Height	2,390 mm	7 ft 9.90 in

Door Opening

Width	2,336 mm	7 ft 8.01 in
Height	2,280 mm	7 ft 5.45 in

Weight

Max Gross	32,500 kg (30,480 kg)	71,650 lb (67,200 lb)
Tare	3,750 kg (3,770 kg)	8,270 lb (8,310 lb)
Max Payload	28,750 kg (26,710 kg)	63,380 lb (58,890 lb)
Load Capacity	68.0(67.4) cubic meters	2,385(2,379) cubic feet



40ft DRY HIGH CUBE

Internal Dimension

Length	12,031 mm	39 ft 5.66 in
Width	2,348 mm	7 ft 8.44 in
Height	2,695 mm	8 ft 10.12 in

Door Opening

Width	2,336 mm	7 ft 8.01 in
Height	2,585 mm	8 ft 5.75 in

Weight

Max Gross	32,500 (30,480) kg	71,650 (67,200) lb
Tare	3,940 (3,990) kg	8,690 (8,860) lb
Max Payload	28,560 (26,490) kg	62,960 (58,400) lb
Load Capacity	76.0 cubic meters	2,689(2,684) cubic feet



45ft DRY HIGH CUBE

Internal Dimension

Length	13,555 mm	44 ft 5.68 in
Width	2,348 mm	7 ft 8.44 in
Height	2,695 mm	8 ft 10.12 in

Door Opening

Width	2,336 mm	7 ft 8.01 in
Height	2,585 mm	8 ft 5.75 in

Weight

Max Gross	32,500 (30,480) kg	71,650 (67,200) lb
Tare	4,880 kg	10,760 lb
Max Payload	27,620 (25,600) kg	60,890 (56,440) lb
Load Capacity	86.0 cubic meters	3,031 cubic feet